



Frameless "Bridger" Roll-Off



Specifications:

Chassis

- Suspension:** 50,000# single point, 3-leaf
- Axles:** (2) 102-inch, 25,000 lb, 5-inch round, common inner/outer bearings
- Hubs:** 10 Hole pilot hub
- Tires:** 11.00x24.5-inch radial
- Brakes:** Air 16-1/2x7-inch cast drum
- ABS:** 2S 1M
- Paint:** One color urethane enamel over primed surface
- Lights:** Sealed beam rubber grommet
- Wiring:** Sealed Harness, 7-wire ATA
- Mud Flaps:** Rear only
- King Pin Plate:** 3/4-inch HT50 (Rocking)
- Back Up Alarm:** Yes
- Rear Impact Guard:** None

Hydraulic Controls: Double acting control valve on King Pin Plate - for operating from ground (this requires standard single line wet kit, plus one return hose to tank. **Note:** Hydraulic reservoir required capacity: Winch Model-50-gallon, Reeving Model-75-gallon

Frame:

- Tilt Frame:** 15-inch HT60 composite
- Draft Arms:** 4x4x1/4-inch Ht50

- Rollers:** (7) 5-inch OD, brass bushings with zerks
- Rollers Top to Ground:** 67-inch front, 61-1/2-inch rear
- Rails Outside:** 35-inch **Inside:** 27-inch
- Hoist Cylinder:** 73-120 double acting
- Body Stop:** Variable position per container
- Container Tie Downs:** Ratchet binders
- Front Nose Sheave:** 12-inch, diagonal, bushed
- Cable:** 7/8-inch diagonal, 68-inch - 6x36 RLL-IWRC with ring hook or Heil hook

Loading System Winch:

- Rated Capacity:** 75,000# (pull to load approx. 75,000# cont.)
- Vertical Lift:** 1st Layer - 55,000#, 2nd Layer - 50,000#
- Reeving Cylinders:** (provides pull to load approx. 54,000# cont.) (2) 7x115-inch stroke
lline pull: 38,484#

Hydraulic Reservoir Req. Cap.

- Winch Model 50-gallon
- Reeving Model 75-gallon



Clement is just "down the road"
Clement's nationwide network of dealers means that Clement quality service and genuine Clement replacement parts are just down the road not across the country.